

Bevestigingsmaterialen-Fasteners-Fixations

Esserstraat 15

B-8550 ZWEVEGEM

Tel : 00 32(0)56 77 19 81

Fax: 00 32(0)56 77 19 82

info@alb.be

www.alb.be

Technische Fiche Fiche Technique

Nylon plug Cheville en nylon

Materialen : Nylon



| Ref | D mm | L mm | Boordiameter Dia du forage | Boordiepte Profond du forage | VERP |
|-------------------|---------|---------|-------------------------------|---------------------------------|--------|
| 11,01,3204 | 4 | 20 | 4mm | 25mm | 500pcs |
| 11,01,3205 | 5 | 25 | 5 | 30 | 500 |
| 11,01,3206 | 6 | 30 | 6 | 35 | 500 |
| 11,01,3208 | 8 | 40 | 8 | 50 | 200 |
| 11,01,3210 | 10 | 50 | 10 | 60 | 100 |
| 11,01,3212 | 12 | 60 | 12 | 70 | 100 |
| 11,01,3214 | 14 | 70 | 14 | 85 | 50 |
| 11,01,3216 | 16 | 80 | 16 | 95 | 50 |

Schroeflengte ?

Dikte te bevestigen stuk+ lengte plug + diameter schroef

| | | |
|----|--------------------------|--------------------|
| VB | Dikte te bevestigen stuk | 25mm |
| | Plug 6,0 x 20 | 20mm |
| | Diam schroef | 5mm |
| | | <hr/> |
| | | 60mm |
| | | Min. Schroeflengte |

Longeur de vis?

Epaisseur de pièce+longeur de cheville+diamètre de vis

| | | |
|-----|-------------------|------------------------|
| Ex. | Epaisseur à fixer | 25mm |
| | Cheville 6,0 x 20 | 20mm |
| | Dia du vis | 5mm |
| | | <hr/> |
| | | 60mm |
| | | Longeur min. De la vis |