

Bevestigingsmaterialen-Fasteners-Fixations

Esserstraat 15

B-8550 ZWEVEGEM

Tel : 00 32(0)56 77 19 81

Fax: 00 32(0)56 77 19 82


info@alb.be

www.alb.be

Technische Fiche Fiche Technique

Universele plug met en zonder kraag Cheville universel avec et sans collerette

Materialen : Nylon



Ref	D mm	L mm	Boordiameter Dia du forage	Boordiepte Profond du forage	Schroeven Vissage	VERP
Met kraag/avec collerette						
	5	32	5mm	40mm	3,5	500pcs
11,04,10640	6	36	6	40	4	500
11,04,10850	8	50	8	60	5	200
11,04,11060	10	60	10	70	6	100
11,04,11270	12	70	12	80	8	100
	14	75	14	85	10	50
Zonder kraag/ sans collerette						
	5	32	5mm	40mm	3,5	500pcs
11,042,0640	6	36	6	40	4	500
11,042,0850	8	50	8	60	5	200
11,042,1060	10	60	10	70	6	100
	12	70	12	80	8	100
	14	75	14	85	10	50

Schroeflengte ?	Dikte te bevestigen stuk+ lengte plug + diameter schroef	
VB	Dikte te bevestigen stuk	25mm
	Plug 8,0 x 50	50mm
	Diam schroef	5mm
		<u>80mm</u> Min. Schroeflengte

Longeur de vis?	Epaisseur de pièce+longeur de cheville+diamètre de vis	
Ex.	Epaisseur à fixer	25mm
	Cheville 8,0 x 50	50mm
	Dia du vis	5mm
		<u>80mm</u> Min. longueur de vis