

Bevestigingsmaterialen-Fasteners-Fixations

Esserstraat 15

B-8550 ZWEVEGEM

Tel : 00 32(0)56 77 19 81

Fax: 00 32(0)56 77 19 82

info@alb.be

www.alb.be



Professionele Digitale Meettoestellen



Lichtmeter



Luchtsnelheidmeter



Vochtigheids-en
Temperatuurmeter



Geluidsmeter

Gebruiksvriendelijk
Kwaliteits/prijsverhouding optimaal
Licht en compacte uitvoering
Groot digitaal display
Voor snelle en eenvoudige metingen
Eénhand bedienbaar
Automatische displayverlichting
Automatische uitschakeling



Set 4

Mini-Light Meter MS 86

- Wide measuring range 0,0...40000lx
- Resolution 0,1lx or 0,1fc
- Automatic Zero calibration
- Easy one-hand operation
- Max-Hold-display
- Auto-off-Function
- Backlight



Applications:

Ideal for monitoring lighting conditions on workplaces, warehouses, industrial and residential buildings. E.g. to meet the adequate lighting in the office or work area.

Technical datas:

Measuring range	0,0...40.000 lx
Resolution	0,1
Accuracy	+ - 5%
Working temperature	0..40 °C
Battery lifetime	Typically 24 hours of continuous operation
Battery	1 x 9 Volt Block battery
Dimensions	157 x 54 x 34mm
Weight	138 g
Art.No.	5020-0886

Mini-Anemometer MS 82

- Measuring range 0,4..25 m/s
- Measuring units: m/s, F/pm, Km/h, Mp/h, knot
- 0,01 m/s resolution
- Easy to use
- Smart and robust
- Auto-off-function
- Max-Avg-display



Applications:

Ideal for easy measurements of ventilation systems in air conditioning. The large display and the keyboard make the instrument easy to use.

- Flow measurements in ventilation ducts (eg at channel outputs)
- Control of filters or hoods
- Measurement of air velocity (workplace inspections)
- Measurement of energy supply

Technical datas:

Flow	
Measuring range	0,4..+25m/s
Resolution	0,01m/s
Accuracy	+3,5% +0,20 m/s of FS
Display	1-line, 7 Segment LCD
Housing	Plastic (ABS)
Size	165 x 54 x 34 mm
Weight	82 g
Power supply	Block battery 9V
Battery lifetime	Ca. 100 hours
Function	Max- Hold-function, Averaging, Unit selection, Low-Bat-indicator
Order.No.	5020-0882

Mini Humidity Meter MS 83

- Fast capacity Humidity Sensor
- 1-second measuring interval
- C/F-switchable
- Max-Min-Hold-Function
- Auto-off-Function
- Backlight



Applications:

Ergonomically designed instrument, ideal for ambient air measurements (HVAC). Temperature and Humidity levels will be quickly identified, eg. Mold in the home. The rugged instrument is standard equipment for industry and trade.

- Construction industry
- Air/Heating(HVAC)
- Education/Schools
- Laboratory
- Food(Storage)

Technical datas:

Temperature

Measuring range	-20..+60 °C
Resolution	0,1 °C
Accuracy	± 0,5°C

Humidity

Measuring range	0..99%rF
Resolution	0,1%
Accuracy	± 3%(20..80%) otherwise ± 4%

Battery	1 x 9 Volt block battery
Dimensions	146 x 54 x 34 mm
Weight	138 g
Art.No	5020-0883

Mini-Sound Level Meter MS 85

- Measuring range 40-130dB
- Resolution 0,1 dB
- Incl. Windshield
- Max-Min-indicator
- Auto-off-Function
- Backlight



Applications:

Ideal for control of the approved noise on workplaces eg. Review by office machines (copiers, printers, etc.)

Technical datas:

Measuring range	40...130 dB
Resolution	0,1 dB
Accuracy	+/- 3,0 dB
Working temperature	0..40 °C
Battery lifetime	Typical 50 hours in continuous operation
Battery	1 x 9 Volt Block battery
Dimensions	157 x 54 x 34 mm
Weight	131 g